

# Lifeline VIEW



## Lifeline VIEW Semi-Automatic Defibrillator

FULL-COLOR VIDEO INSTRUCTION DELIVERS BREAKTHROUGH EASE-OF-USE

The Lifeline VIEW makes it easy for anyone — from first responders to untrained bystanders — to respond confidently and appropriately during an emergency. This revolutionary life-saving device combines a sleek, user-friendly design with military-grade specifications—including the most proven biphasic waveform. It's also the first and only AED with a full-color interactive display that shows step-by-step videos for performing CPR, rescue breathing and external defibrillation.

You can also be confident that the device will be easy to maintain and ready for rescue. The Lifeline VIEW provides clear guidance for using and maintaining the device. Additionally, it has been designed to support upgrades and enhancements.

Like the original award-winning Defibtech AED, the Lifeline VIEW includes all the mission-critical features necessary to provide the most advanced cardiac treatment and exceeds the American Heart Association performance recommendations.

# Lifeline VIEW Semi-Automatic Defibrillator

## TECHNICAL SPECIFICATIONS\*

### DEFIBRILLATOR

#### TYPE

Semi-Automatic external defibrillator

#### MODEL

DDU-2300 series

#### WAVEFORM

Biphasic Truncated Exponential  
(Impedance compensated)

#### ENERGY

Adult: 150 Joules  
Child / Infant: 50 Joules  
(Nominal into 50 Ohm load)

#### CONTROLS

Lighted On/Off button  
Lighted Shock button

#### CHARGE TIME\*\*

Less than 4 seconds  
(shock decision to shock)

#### DISPLAY

High-resolution color LCD

#### VIDEO PROMPTS

Full motion video  
On-screen text prompts

#### CPR COACHING

Video and voice coaching  
On-demand video help

#### VOICE PROMPTS

Extensive voice prompts guide  
user through operation of the unit

#### RESCUE PROTOCOL

AHA/ERC 2010  
Supports protocol updates by  
the user (password protected)

\*\*Typical, with new battery at 25° C

### PATIENT ANALYSIS SYSTEM

#### PATIENT ANALYSIS

Automatically evaluates patient  
impedance for proper pad contact.  
Monitors signal quality and analyzes  
patient ECG for shockable/  
non-shockable rhythms.

#### SENSITIVITY/SPECIFICITY

Meets AAMI-DF-80 specifications  
and AHA recommendations

### BATTERY PACK

#### MODEL

DBP-2003

#### POWER

12V, 2800 mAh

#### TYPE

Lithium/Manganese Dioxide  
Disposable, recyclable,  
non-rechargeable

#### CAPACITY\*\*

125 shocks or 8 hours  
continuous operation

#### STANDBY LIFE\*\*

4 years

#### LOW BATTERY INDICATORS

Visible  
Audible

\*\*Typical, with new battery at 25° C

### SELF TESTS

#### AUTOMATIC

Automatic daily, weekly and  
monthly circuitry tests

#### BATTERY INSERTION

System integrity test on battery  
insertion

#### PAD PRESENCE

Pads preconnected tested daily

#### USER-INITIATED

Unit and battery pack system  
test initiated by the user

#### STATUS INDICATION

Visual and audible indication of  
unit status

#### STATUS SCREEN

Unit self-test results  
Pads and battery information  
(status and expiration)

### DEFIBRILLATION / MONITORING PADS

#### MODEL

Adult – DDP-2001  
Child / Infant – DDP-2002

#### TYPE

Pre-connected, single-use,  
non-polarized, disposable,  
self-adhesive electrodes with  
cable and connector

#### SURFACE AREA

77 cm<sup>2</sup> (nominal, each pad)  
50 cm<sup>2</sup> (nominal, each pad)

### EVENT DOCUMENTATION

#### INTERNAL EVENT RECORD

Critical ECG segments and rescue  
event parameters are recorded  
(greater than 60 minutes) and  
can be downloaded to a removable  
data card

#### PC-BASED EVENT REVIEW

ECG with event tag display, and  
audio playback when available

#### REMOVABLE STORAGE

(optional) Up to 30 hours of ECG  
and event data storage (no audio  
option) or up to 3 hours of audio  
(audio option). ECG and event  
storage on a removable data card.  
Actual length of storage is  
dependent on card capacity.

#### USB PORT

Event download and  
maintenance operations

### ENVIRONMENTAL

#### TEMPERATURE

Operating: 0 to 50°C (32 to 122°F)  
Standby: 0 to 50°C (32 to 122°F)

#### RELATIVE HUMIDITY

Operating / Standby: 5%-95%  
(non-condensing)

#### ALTITUDE

-500 to 15,000 ft (-150 to 4500 m)  
per MIL-STD-810F 500.4 Procedure II

#### VIBRATION

Ground (MIL-STD-810F 514.5  
Category 20)

Helicopter (RTCA/DO-160D,  
Section 8.8.2, Cat R, Zone 2,  
Curve G)

Jet Aircraft (RTCA/DO-160D  
Section 8, Cat H, Zone 2,  
Curves B & R)

#### SHOCK / DROP ABUSE TOLERANCE

MIL-STD-810F 516.5 Procedure IV  
48 inches (1.2 meters), any edge,  
corner, or surface, in standby mode

#### CRUSH TEST

1,000 pounds (450 kg)

#### SEALING / WATER RESISTANCE

IEC60529 class IP55; Protected  
against dust and waterjets  
(battery pack installed)

#### ESD

EN61000-4-2: (Open air up to  
8kV or direct contact up to 6kV)

#### EMC (Emission)

CISPR 11 Group 1 Level B and  
FCC Part 15

#### EMC (Immunity)

IEC 61000-4-3 and IEC 61000-4-8

### PHYSICAL

#### SIZE

7.3 x 9.5 x 2.3 Inches  
(18.5 x 24 x 5.8 cm)

#### WEIGHT

Less than 3 lbs (1.4 kg)  
(with battery)

\*Specifications subject to change without notice